1424 Series

Level T-6, E-5, O-5, P-7
NSA/CSS EPL Listed for Paper, Key Tape, CDs



Global Leader in High Security Information End-of-Life Solutions for Over 50 Years

Specifications:

Media Accepted	Paper, optical, small e-media	
Final Particle Size	2mm - 5mm, screen dependent	
Cycle Capacity	Media dependent	
Hourly Throughput	Up to 1,200 lbs. (NSA rated) Up to 2,400 lbs.	
Feed Opening	14 in. x 24 in.	
Dimensions (HxWxD) Weight	74 in. x 80 in. x 65 in. 6,200 lbs.	
Electrical Power	3-Phase 208/230/460/575V-60Hz International voltage available 60HP (75HP or 100HP available)	
Hourly Throughput Feed Opening Dimensions (HxWxD) Weight	Up to 1,200 lbs. (NSA rated) Up to 2,400 lbs. 14 in. x 24 in. 74 in. x 80 in. x 65 in. 6,200 lbs. 3-Phase 208/230/460/575V-60Hz	



Standard Features:

- Solid steel rotors with eight hold-down bolts per blade for maximum performance and durability
- Safety limit switches
- Low base with air transition for security evacuation
- Equipped with 7 in. transition
- Heavy duty system for high volume applications
- Made in the USA TAA compliant

Options and Accessories:

- · Replacement/spare knives and screens
- Conveyor feed hopper
- International voltage
- At-site set-up, installation, training
- Preventive maintenance contract
- Extended warranty

Model	1424	1424/5
Cutting System	5 blade (3 rotor, 2 bed)	7 blade (5 rotor, 2 bed)
Capacity: NSA Evaluated	800 lbs./hr.	1,200 lbs./hr.
Capacity	1,200 lbs./hr.	2,400 lbs./hr.