

# IMPORTANT READ BEFORE OPERATING

The crusher must be installed according to Customer's incoming power; as in a 115 volt unit must be installed on a 110-120V/1/60Hz, grounded electrical line service with the crusher equipped with a 15 Amp (3) three prong plug on the power cord. If unit is 230 volt it must be installed on a 220-240V/1/50Hz grounded electrical line service, with the standard crusher being equipped with a 2 prong European plug on the power cord.

After removing the crusher from its packaging, be sure that all paperwork and any loose items that may have been shipped with the crusher have been removed from the packaging as well. *Please note that all packaging should be retained by customer for (30) days from the time of receipt. In the event that this unit needs to be sent back for replacement or repair this packaging will be required to do so. Should the packaging have been discarded before the (30) day requested period, packaging costs will be incurred by the customer.*

Be sure to place the crusher on a strong and sturdy surface.

**IMPORTANT:** Replace the reservoir plug with the supplied breather plug prior to using this unit. **DO NOT OPERATE THE CRUSHER WITH THE SOLID SHIPPING PLUG IN THE RESERVOIR!**  
**NOTE:** Retain the red shipping plug. It **MUST** be reinstalled for **ANY** shipping or transportation to prevent fluid leakage!

The reservoir plug is located on the back side of the crusher cabinet. With the crusher still unplugged, locate the back panel on the crusher. This panel is secured by (6) phillips head screws. Remove screws and slide panel next to the crusher.



Remove Back Plate.

Remove shipping plug and replace with the supplied breather plug for operation. Shipping plug must be retained and reused for ANY transporting or shipping.

**WARNING: THE CRUSHER IS DESIGNED FOR CRUSHING HARD DRIVES UP TO 1.65 INCH. TRYING TO CRUSH OBJECTS / MATERIAL OTHER THAN HARD DRIVES WILL VOID THE WARRANTY. MANUFACTURER IS NOT RESPONSIBLE FOR FAILURE OF THIS UNIT IF CUSTOMER USES UNIT FOR SOMETHING IT WAS NOT INTENDED FOR.**