

3000 Dual Stage Disintegrator

Level T-6, E-5, O-5, P-7
NSA/CSS EPL Listed for Paper, Key Tape, CDs



Global Leader in High Security Information
End-of-Life Solutions for Over 50 Years

Specifications:

Media Accepted	Paper, optical, small e-media
Final Particle Size	2mm - 25mm, screen dependent
Cycle Capacity	Media dependent
Hourly Throughput	Up to 1,200 lbs. (NSA rated) Up to 2,400 lbs.
Feed Opening	12 in. x 24 in.
Dimensions (HxWxD) Weight	120 in. x 78 in. x 60 in. 5,000 lbs.
Electrical	3-phase 208/230/460/575V-60Hz International voltage available
Power	30 HP
Warranty	5 year non-wear parts/90 days labor

Standard Features:

- Solid steel rotors with eight hold-down bolts per blade for maximum performance and durability
- Safety limit switches
- Interlocked bulk pre-shredder
- Low base with air transition for security evacuation
- Equipped with 7 in. transition
- Heavy duty system for high volume applications
- Particle size 2mm - 25mm depending on screen size
- Up to 2,400 lbs./hr.
- Made in the USA — TAA compliant

Options and Accessories:

- MX steel sound enclosure
STC37 or STC40
- Replacement/spare knives and screens
- International voltage
- At-site set-up, installation, training
- Preventive maintenance contract
- Waste bag collection
- Recyclable briquette collection
- Interlocked feed conveyor
- Extended warranty

