

# DC-S1-3 SSD

Level E-3, T-1, O-2

Solid State Shredder



Global Leader in High Security Information  
End-of-Life Solutions for Over 50 Years

## Specifications:

Media Accepted	SSDs up to 1.5 in. thick, magnetic tape, thumb drives, flash, and optical
Final Particle Size	0.375 in. (9.5mm) W x random H
Cycle Capacity	One at a time
Hourly Throughput	Up to 200 3.5 in. drives Up to 600 2.5 in. drives
Feed Opening	10.5 in. x 1.5 in each
Waste Collection	Internal bin
Dimensions (HxWxD)	48.75 in. x 57 in. x 22.5 in.
Weight	1,830 lbs.
Electrical Power	3-phase 208/230/460-60Hz 3HP
Warranty	1 year non-wear parts/90 days labor

## Standard Features:

- Designed for data centers, offices, or limited spaces
- Accepts solid state drives (SSDs) and devices up to 1.5 in. thick
- Also shreds items such as data tapes, cell phones, optical media, PCBs, and other related electronic storage media
- High torque for destruction of enterprise media
- Includes easy-to-use operator interface with features such as auto reverse and bin collection sensors
- Includes carbon pre-filter and HEPA filtration for ultimate operator and environmental healthy and safety
- Steel fork pockets
- Small footprint allows for easy, versatile placement
- Shredded material is discharged into a convenient collection bin housed within the system cabinet
- Safety limit switches on all doors
- Made in the USA — TAA compliant

## Options and Accessories:

- Replacement waste collection bin
- International voltage
- CE Marking
- Maintenance tool kit
- At-site set-up, installation, training
- Preventive maintenance contract
- Extended warranty

